

Myfridgeonline



Introducing the New **Myfridgeonline WI-FI logger** which offers SMS/Email notifications of Temperature & Humidity Violations as well as recording the information to the Cloud enabling remote real time access to your current and historic information and automated reporting straight to your email.

Features:

- Online Access
- Dashboard
- Graphs
- Alerts (SMS and or Email)
- Detailed Autonomous Reports send to email
- Audit Logs
- User Hierarchy

Suitable for use in:

- Fridge
- Freezer
- Cold-room
- Room
- Incubator
- Server-Rooms...



WI-FI LOGGER

General

Model	WIFI I/E-T/TH
Dimensions	80x52x40
Weight	0.1kg
Mounting method	Velcro/Two way tape/Hang
Mode of Communication	WIFI
Mode of operation	Electronic
ICASA Approval	TA-2018/2266

Environmental Specifications

Operating Temperature	5°C to 60°C
IP Rating	IP 44
Storage Temperature	5°C to 50°C

Electrical Specifications

Power Supply	100 – 220Vac Adaptor with 5vdc output, 500mA USB A Female
Cable	Male USB 2.0 A to Male Micro B USB

Communication

Bandwidth Standard	802.11 b/g/n
Range	50m to 100m Line of sight (environment dependant)

Logging

Logging Interval	Default: 10 Minutes Minimum: 10 Minute Maximum: 1440 Minutes (Configurable in 1 minute step duration)
Standard Upload Frequency	Default: 10 Minutes Minimum: 10 Minute Maximum: 1440 Minutes (Configurable in 10 minute step duration)
Memory capability	80 logs internal EPROM

User Interface

Viewing and Programming	WEB (www.myfridgeonline.com)
-------------------------	--

Alarms

External	SMS, Email & WEB
----------	------------------

Quality

Standard	ISO 9001-2015
----------	---------------

Internal Temperature Humidity Sensor

Digital Probes	1
Sensor Temperature Range	-30°C to +60°C
Sensor Temperature Accuracy	±0.3°C
Sensor Humidity Range	0 to 100%
Sensor Humidity Accuracy	±2%